NSN 5950-00-752-4679

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-752-4679

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.688 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.562 inches single mounting facility single center group

Inductance Type:

Fixed

Inductance Rating:

15.00 henry single component single winding

Frequency Rating:

120.0 hertz single component

Body Length:

2.312 inches

Body Width:

2.062 inches

Body Height:

3.125 inches

Maximum Operating Temp:

105.0 degrees celsius

Winding Quantity:

1 single component

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Rating Method:

Electrical single component single winding

Thread Size:

0.138 inches single group

Winding Operating Current:

60.0 milliamperes dc single component single winding

Dc Resistance Rating In Ohms:

230.000 single component single winding

Test Data Document:

81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

2 turret

NSN 5950-00-752-4679

Reactor - Page 2 of 2



Spec	ifi	cation	Data
------	-----	--------	------

96906-ms16465 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0