## NSN 5950-00-752-4699

Power Transformer - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5950-00-752-4699   |
|---|
| Center To Center Distance Between Mounting Facilities Parallel To Length:   |
| 7.000 inches single mounting facility single center group   |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 5.000 inches single mounting facility single center group   |
| Mounting Hole Diameter:   |
| 0.438 inches single group   |
| Frequency Rating:   |
| 60.0 hertz single component   |
| Input-output Phase Relationship:  |
| Single phase to single phase single component   |
| Body Length:  |
| 9.250 inches  |
| Body Width:   |
| 7.531 inches  |
| Body Height:  |
| 7.438 inches  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Flange single group and unthreaded hole single group  |
| Winding Function And Quantity:  |
| 1 primary single component and 1 secondary single component   |
| Winding Operating Voltage:  |
| 450.00 ac pounds per hour wet single component single primary   |
| Special Features:   |
| Impedance voltage rating 1.6 percent  |
| Test Data Document:   |
| 81349-mil-t-16315 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing |
| etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)                     |
| Terminal Type And Quantity:   |
| 4 wire lead   |
| Specification Or Standard:  |
| Cc type   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| <del></del>   |

No

Fiig:

A058b0

Demilitarization: