## NSN 5950-00-754-7054

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-754-7054

| Reliability Indicator:  |
|---|
| Not established   |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.750 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 1.750 inches single mounting facility single center group                 |
| Frequency Rating:   |
| 350.0 hertz single component and 1.2 kilohertz single component           |
| Input-output Phase Relationship:  |
| Single phase to single phase single component                             |
| Body Length:  |
| 6.500 inches  |
| Body Width:   |
| 3.250 inches  |
| Body Height:  |
| 3.250 inches  |
| Inclosure Type:   |
| Open  |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Threaded hole single group  |
| Winding Function And Quantity:  |
| 1 primary, variable autotransformer type single component                 |
| Thready Qty Per Inch (tpi):   |
| 32 single group   |
| Thread Size:  |
| 0.190 inches single group   |
| Winding Operating Current:  |
| 2.0 amperes ac single component single secondary                          |
| Winding Operating Voltage:  |
| 115.00 ac volts single component single primary                           |
| Thread Series Designator:   |
| Unf single group  |
| Terminal Type And Quantity:   |
| 3 threaded stud   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |

No

## NSN 5950-00-754-7054

Power Transformer - Page 2 of 2



Fiig:

A058b0