

View Online at <https://aerobasegroup.com/nsn/5950-00-754-9312>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.062 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.031 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

3.810 inches

Body Width:

3.750 inches

Body Height:

3.560 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 5 secondary single component

Thread Size:

0.164 inches single group

Winding Operating Current:

70.0 milliamperes dc single component 1st secondary and 175.0 milliamperes dc single component 1st secondary

Winding Operating Voltage:

115.00 ac volts single component single primary

Special Features:

Primary winding; 5secondary windings

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

18 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0