

View Online at <https://aerobasegroup.com/nsn/5950-00-754-9312>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.062 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.031 inches single mounting facility single center group

**Frequency Rating:**

400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to core single component

**Body Length:**

3.810 inches

**Body Width:**

3.750 inches

**Body Height:**

3.560 inches

**Inclosure Type:**

Open

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded hole single group

**Winding Function And Quantity:**

1 primary single component and 5 secondary single component

**Thread Size:**

0.164 inches single group

**Winding Operating Current:**

70.0 milliamperes dc single component 1st secondary and 175.0 milliamperes dc single component 1st secondary

**Winding Operating Voltage:**

115.00 ac volts single component single primary

**Special Features:**

Primary winding; 5secondary windings

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

18 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0