NSN 5950-00-754-9544

Power Autotransformer Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-754-9544

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Corrosion resistant and vibration resistant and humidity resistant

Overall Length:

Between 4.710 inches and 4.790 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.359 inches single mounting facility single center group and 3.391 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.359 inches single mounting facility single center group and 3.391 inches single mounting facility single center group

Overall Width:

4.250 inches

Frequency Rating:

400.0 hertz single component and 800.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Height:

4.125 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary, variable autotransformer type single component

Thread Size:

0.190 inches single group

Winding Operating Current:

3.0 amperes ac single component single primary output

Winding Power Rating:

0.42 kilovolt-amperes single component single primary output

Winding Operating Voltage:

120.00 ac volts single component single primary input

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5950-00-754-9544

Power Autotransformer Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0