## NSN 5950-00-754-9544

Power Autotransformer Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-754-9544

## **Reliability Indicator:**

Not established

#### **Hazardous Locations/environmental Protection:**

Corrosion resistant and vibration resistant and humidity resistant

#### **Overall Length:**

Between 4.710 inches and 4.790 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

3.359 inches single mounting facility single center group and 3.391 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.359 inches single mounting facility single center group and 3.391 inches single mounting facility single center group

#### **Overall Width:**

4.250 inches

#### Frequency Rating:

400.0 hertz single component and 800.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### **Body Height:**

4.125 inches

## **Inclosure Type:**

Open

## **Mounting Facility Quantity:**

4 single group

#### **Mounting Method:**

Threaded hole single group

## **Winding Function And Quantity:**

1 primary, variable autotransformer type single component

## **Thread Size:**

0.190 inches single group

## **Winding Operating Current:**

3.0 amperes ac single component single primary output

## **Winding Power Rating:**

0.42 kilovolt-amperes single component single primary output

## **Winding Operating Voltage:**

120.00 ac volts single component single primary input

#### **Thread Series Designator:**

Unc single group

## **Terminal Type And Quantity:**

4 tab, solder lug

## Shelf Life:

N/a

#### **Unit Of Measure:**

--

# NSN 5950-00-754-9544

Power Autotransformer Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0