

View Online at <https://aerobasegroup.com/nsn/5950-00-754-9954>

Reliability Indicator:

Not established

Overall Length:

1.703 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.120 inches single mounting facility single center group and 1.130 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.807 inches single mounting facility single center group and 0.817 inches single mounting facility single center group

Transformer Function:

Modulation

Impedance Rating In Ohms:

5024.0 single component single primary

Frequency Rating:

400.0 hertz single component

Primary To Secondary Turn Ratio:

1 to 15 single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Width:

1.219 inches

Body Height:

1.391 inches

Maximum Operating Temp:

170.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.112 inches single group

Winding Operating Current:

20.0 milliamperes dc single component single primary

Test Data Document:

95750-8050000628 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

5 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0