NSN 5950-00-755-7074

Power Autotransformer Transformer - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5950-00-755-7074 |
|---|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.125 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 3.125 inches single mounting facility single center group |
| Mounting Hole Diameter: |
| 0.250 inches single group |
| Frequency Rating: |
| 50.0 hertz single component and 60.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Body Length: |
| 4.500 inches |
| Body Width: |
| 3.750 inches |
| Body Height: |
| 3.750 inches |
| Inclosure Type: |
| Partially enclosed, half shell |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Flange single group and unthreaded hole single group |
| Winding Function And Quantity: |
| 1 primary, variable autotransformer type single component |
| Winding Operating Current: |
| 3.7 amperes ac single component single primary output |
| Winding Power Rating: |
| 40.0 volts-amperes single component single primary output |
| Winding Operating Voltage: |
| 120.00 ac volts single component single primary input |
| Terminal Type And Quantity: |
| 3 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

Fiig:

A058b0