

View Online at <https://aerobasegroup.com/nsn/5950-00-755-7900>

**Reliability Indicator:**

Not established

**Impedance Rating In Ohms:**

50.0 single component single secondary and 250.0 single component single secondary and 600.0 single component single secondary

**Frequency Rating:**

300.0 hertz single component and 7.0 kilohertz single component

**Maximum Transformer Power Rating:**

10.0 decibels single component

**Winding Shielding Method:**

Internal shield brought out to terminal single component

**Body Length:**

1.781 inches

**Body Outside Diameter:**

0.938 inches

**Distance Between Mounting Facility Centers:**

0.562 inches single mounting facility single center group

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

2 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Thready Qty Per Inch (tpi):**

40 single group

**Thread Size:**

0.112 inches single group

**Winding Operating Current:**

3.0 milliamperes dc single component single primary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

7 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0