## NSN 5950-00-757-9263

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-757-9263

Reliability Ind	licator:
-----------------	----------

Not established

## Center To Center Distance Between Mounting Facilities Parallel To Length:

2.437 inches single mounting facility single center group

## Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group

#### Frequency Rating:

48.0 hertz single component and 62.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### **Winding Shielding Method:**

Internal shield grounded to inclosure and core single component

**Body Length:** 

3.875 inches

**Body Width:** 

3.312 inches

**Body Height:** 

4.000 inches

## Inclosure Type:

Hermetically sealed

## **Mounting Facility Quantity:**

4 single group

#### **Mounting Method:**

Threaded stud single group

## **Winding Function And Quantity:**

1 primary single component and 2 secondary single component

## Thready Qty Per Inch (tpi):

32 single group

## Thread Size:

0.190 inches single group

## **Winding Operating Current:**

7.0 amperes ac single component 1st secondary

## **Winding Operating Voltage:**

6.30 ac volts single component 1st secondary

## **Thread Series Designator:**

Unf single group

## **Terminal Type And Quantity:**

6 tab, solder lug

## Shelf Life:

N/a

#### **Unit Of Measure:**

--

# NSN 5950-00-757-9263

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0