NSN 5950-00-760-1413

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-760-1413

| Poliobility Indicator |
|---|
| Reliability Indicator: |
| |
| Overall Height: |
| Between 2.062 inches and 2.250 inches |
| Frequency Rating: |
| 60.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Winding Shielding Method: |
| Internal shield grounded to inclosure and core single component |
| Body Length: |
| Between 1.250 inches and 1.312 inches |
| Body Width: |
| Between 1.250 inches and 1.312 inches |
| Body Height: |
| Between 1.625 inches and 1.750 inches |
| Distance Between Mounting Facility Centers: |
| 1.234 inches single mounting facility single center group and 1.266 inches single mounting facility single center group |
| |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 2 single group |
| Mounting Method: |
| Threaded stud single group |
| Winding Function And Quantity: |
| 1 primary single component and 1 secondary single component |
| Thready Qty Per Inch (tpi): |
| 32 single group Thread Size: |
| |
| 0.138 inches single group Winding Operating Current: |
| 20.0 milliamperes dc single component single secondary |
| Winding Operating Voltage: |
| 6.00 ac volts single component single secondary |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 4 solder stud |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| |

NSN 5950-00-760-1413

Power Transformer - Page 2 of 2

Demilitarization:

No

Fiig:

A058b0

