

View Online at <https://aerobasegroup.com/nsn/5950-00-761-3692>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.859 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.297 inches single mounting facility single center group

Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core and brought out to terminal single component

Body Length:

Between 2.937 inches and 3.062 inches

Body Width:

Between 2.500 inches and 2.625 inches

Body Height:

Between 4.062 inches and 4.250 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

200.0 milliamperes ac single component all secondary

Winding Operating Voltage:

203.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

13 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0