NSN 5950-00-761-6676

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-761-6676

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.609 inches single mounting facility single center group and 2.641 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.109 inches single mounting facility single center group and 2.141 inches single mounting facility single center group

Inductance Type:

Swinging

Inductance Rating:

12.00 henry single component single winding and 20.00 henry single component single winding

Frequency Rating:

60.0 hertz single component

Body Length:

Between 3.438 inches and 3.563 inches

Body Width:

Between 2.938 inches and 3.063 inches

Body Height:

Between 4.687 inches and 4.875 inches

Maximum Operating Temp:

105.0 degrees celsius

Winding Quantity:

1 single component

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Rating Method:

Electrical single component single winding

Thread Size:

0.164 inches single group

Winding Operating Current:

85.0 milliamperes dc single component single winding and 125.0 milliamperes dc single component single winding

Dc Resistance Rating In Ohms:

100.000 single component single winding

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

NSN 5950-00-761-6676

Reactor - Page 2 of 2



| ı | 1 | n | iŧ | 1 | : N/ | lea | | | _ | |
|---|---|---|----|----------|------|-----|-----|----|---|---|
| ı | u | n | IT | OI | ١V | ıea | เรเ | JI | е | : |

--

Demilitarization:

No

Fiig:

A058b0