## NSN 5950-00-761-6676

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-761-6676

#### **Reliability Indicator:**

Not established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

2.609 inches single mounting facility single center group and 2.641 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.109 inches single mounting facility single center group and 2.141 inches single mounting facility single center group

#### **Inductance Type:**

Swinging

#### **Inductance Rating:**

12.00 henry single component single winding and 20.00 henry single component single winding

#### Frequency Rating:

60.0 hertz single component

#### **Body Length:**

Between 3.438 inches and 3.563 inches

#### **Body Width:**

Between 2.938 inches and 3.063 inches

#### **Body Height:**

Between 4.687 inches and 4.875 inches

#### **Maximum Operating Temp:**

105.0 degrees celsius

## Winding Quantity:

1 single component

#### **Inclosure Type:**

Hermetically sealed

## **Mounting Facility Quantity:**

4 single group

## **Mounting Method:**

Threaded stud single group

#### **Rating Method:**

Electrical single component single winding

#### **Thread Size:**

0.164 inches single group

## **Winding Operating Current:**

85.0 milliamperes dc single component single winding and 125.0 milliamperes dc single component single winding

## Dc Resistance Rating In Ohms:

100.000 single component single winding

## **Thread Series Designator:**

Unc single group

#### **Terminal Type And Quantity:**

2 tab, solder lug

## Shelf Life:

N/a

# NSN 5950-00-761-6676

Reactor - Page 2 of 2



| ı | 1 | n | iŧ | <b>1</b> | : N/ | lea |     |    | _ |   |
|---|---|---|----|----------|------|-----|-----|----|---|---|
| ı | u | n | IT | OI       | ١V   | ıea | เรเ | JI | е | : |

--

Demilitarization:

No

Fiig:

A058b0