## NSN 5950-00-761-9156

Radio Frequency Coil - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-761-9156

| Reliability Indicator:  |
|---|
| Not established   |
| Inductance Rating:  |
| 4.10 microhenries single component single winding and 7.30 microhenries single component single winding |
| Coil Form Type:   |
| Hollow single component   |
| Core Construction:  |
| Powdered single component   |
| Adjustment Device Drive Type:   |
| Slotted screw single component  |
| Body Length:  |
| 0.850 inches  |
| Body Outside Diameter:  |
| 0.580 inches  |
| Inclosure Type:   |
| Open  |
| Mounting Method:  |
| Threaded bushing single group   |
| Rating Method:  |
| Electrical single component single winding  |
| Thready Qty Per Inch (tpi):   |
| 32 single group   |
| Thread Size:  |
| 0.190 inches single group   |
| Winding Operating Current:  |
| 1.0 amperes dc single component single winding  |
| Dc Resistance Rating In Ohms:   |
| 0.350 single component single winding   |
| Quality Factor:   |
| 75 single component single winding  |
| Adjustment Method And Quantity:   |
| 1 adjustable core single component  |
| Thread Series Designator:   |
| Unf single group  |
| Terminal Type And Quantity:   |
| 2 tab, solder lug   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |

No

## NSN 5950-00-761-9156

Radio Frequency Coil - Page 2 of 2



Fiig:

A058b0