NSN 5950-00-762-3149

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-762-3149

Delichility Indicator
Reliability Indicator:
Not established
Hazardous Locations/environmental Protection:
Dustproof
Center To Center Distance Between Mounting Facilities Parallel To Length:
4.360 inches single mounting facility single center group and 4.390 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
4.234 inches single mounting facility single center group and 4.266 inches single mounting facility single center group
Inductance Type:
Fixed
Inductance Rating:
1.00 henry single component single winding
Frequency Rating:
50.0 hertz single component
Body Length:
5.500 inches
Body Width:
5.000 inches
Body Height:
6.500 inches
Maximum Operating Temp:
130.0 degrees celsius
Winding Quantity:
1 single component
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded stud single group
Rating Method:
Electrical single component single winding
Thread Size:
0.250 inches single group
Winding Operating Current:
2.0 amperes dc single component single winding
Dc Resistance Rating In Ohms:
9.000 single component single winding

Unc single group

Terminal Type And Quantity:

Thread Series Designator:

2 tab, solder lug

NSN 5950-00-762-3149

Reactor - Page 2 of 2



	L -	11		ife	_
3	ne	п	_	пе	Ξ

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0