## NSN 5950-00-762-3152

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-762-3152

## **Reliability Indicator:**

Not established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

4.546 inches single mounting facility single center group and 4.578 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.421 inches single mounting facility single center group and 3.453 inches single mounting facility single center group

#### Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### **Maximum Transformer Power Rating:**

300.0 volt-ampere single component

#### Winding Shielding Method:

Core grounded single component

#### **Body Length:**

5.453 inches

#### **Body Width:**

4.390 inches

#### **Body Height:**

6.625 inches

## **Maximum Operating Temp:**

130.0 degrees celsius

#### **Inclosure Type:**

Fully enclosed

#### **Mounting Facility Quantity:**

4 single group

## **Mounting Method:**

Threaded stud single group

## Winding Function And Quantity:

1 primary single component and 1 secondary single component

#### **Thread Size:**

0.312 inches single group

### **Winding Operating Current:**

12.6 amperes ac single component single secondary

#### **Winding Operating Voltage:**

57.00 ac volts single component single primary and 420.00 ac volts single component single primary and 440.00 ac volts single component single primary and 460.00 ac volts single component single primary

## **Thread Series Designator:**

Unc single group

## **Terminal Type And Quantity:**

8 threaded stud

#### Shelf Life:

N/a

# NSN 5950-00-762-3152

Power Transformer - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A058b0