NSN 5950-00-763-2247

Saturable Reactor - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5950-00-763-2247

Reliability Indicator:
Not established
Frequency Rating:
800.0 hertz single component
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
2 single group
Mounting Method:
Threaded hole single group
Winding Function And Quantity:
1 primary and 2 control single component
Thready Qty Per Inch (tpi):
40 single group
Thread Size:
0.112 inches single group
Dc Resistance Rating In Ohms:
15.000 single component all control
15.000 single component all control Winding Operating Voltage:
Winding Operating Voltage:
Winding Operating Voltage: 54.00 ac volts single component single primary
Winding Operating Voltage: 54.00 ac volts single component single primary Thread Series Designator:
Winding Operating Voltage: 54.00 ac volts single component single primary Thread Series Designator: Unc single group
Winding Operating Voltage: 54.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity:
Winding Operating Voltage: 54.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 6 tab, solder lug
Winding Operating Voltage: 54.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 6 tab, solder lug Shelf Life:
Winding Operating Voltage: 54.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 6 tab, solder lug Shelf Life: N/a
Winding Operating Voltage: 54.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 6 tab, solder lug Shelf Life: N/a
Winding Operating Voltage: 54.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 6 tab, solder lug Shelf Life: N/a Unit Of Measure:
Winding Operating Voltage: 54.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 6 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization:
Winding Operating Voltage: 54.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 6 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No