NSN 5950-00-763-6766

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-763-6766
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
6.500 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
4.187 inches single mounting facility single center group
Mounting Hole Diameter:
0.375 inches single group
Inductance Type:
Fixed
Inductance Rating:
4.00 henry single component single winding
Body Length:
5.750 inches
Body Width:
5.250 inches
Body Height:
7.250 inches
End Application:
Arsr-2, fa-7011 transmitter/modulator cabinet
Winding Quantity:
1 single component
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
4 single group
Mounting Method:
Flange single group and unthreaded hole single group
Winding Operating Current:
300.0 milliamperes dc single component single winding
Dc Resistance Rating In Ohms:
400.000 single component single winding
Special Features:
65 kv dc input, 400 ohms; function, reactor, 4 hy, charging choke; reference data, I-101, instruction book arsr-2, vol 5, sec 10, pg
10-41
Terminal Type And Quantity:
2 standoff, solder lug
Shelf Life:
N/a
Unit Of Measure:

No

Demilitarization:

NSN 5950-00-763-6766

Reactor - Page 2 of 2



Fiig:

A058b0