## NSN 5950-00-763-8794

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-763-8794
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.190 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.020 inches single mounting facility single center group
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield brought out to terminal single component
Body Length:
1.450 inches
Body Width:
1.320 inches
Body Height:
1.140 inches
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded hole single group
Winding Function And Quantity:
1 primary single component and 1 secondary single component
Thready Qty Per Inch (tpi):
40 single group
Thread Size:
0.112 inches single group
Winding Operating Voltage:
162.00 ac volts single component single secondary and 180.00 ac volts single component single secondary or 192.00 ac volts single
component single secondary
Test Data Document:
03538-77c709208 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
7 tab, solder lug
Reference Number Differentiating Characteristics:
Test data document
Shelf Life:

--

N/a

**Unit Of Measure:** 

## NSN 5950-00-763-8794

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0