

View Online at <https://aerobasegroup.com/nsn/5950-00-763-8794>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.190 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.020 inches single mounting facility single center group

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

1.450 inches

Body Width:

1.320 inches

Body Height:

1.140 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Qty Per Inch (tpi):

40 single group

Thread Size:

0.112 inches single group

Winding Operating Voltage:

162.00 ac volts single component single secondary and 180.00 ac volts single component single secondary or 192.00 ac volts single component single secondary

Test Data Document:

03538-77c709208 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

7 tab, solder lug

Reference Number Differentiating Characteristics:

Test data document

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0