NSN 5950-00-764-1092

Power Transformer - Page 1 of 2





View Online at https://aerobasegroup.com/nsn/5950-00-764-1092

| Reliability Indicator: | |
|---|---------|
| Not established | |
| Overall Height: | |
| 4.812 inches | |
| Mounting Hole Diameter: | |
| 0.219 inches single group | |
| Frequency Rating: | |
| 50.0 hertz single component and 60.0 hertz single component | |
| Input-output Phase Relationship: | |
| Single phase to single phase single component | |
| Winding Shielding Method: | |
| Internal shield grounded to inclosure and core single component | |
| Body Length: | |
| 4.031 inches | |
| Body Width: | |
| 3.250 inches | |
| Body Height: | |
| 4.250 inches | |
| Inclosure Type: | |
| Hermetically sealed | |
| Mounting Facility Quantity: | |
| 6 single group | |
| Mounting Method: | |
| Unthreaded hole single group | |
| Winding Function And Quantity: | |
| 1 primary single component and 2 secondary single component | |
| Center To Center Distance Between Mounting Facilities Parallel To The Base Of An Isosceles Triar | ngle: |
| 2.250 inches single mounting facility single center group | |
| Winding Operating Current: | |
| 500.0 milliamperes ac single component 2nd secondary | |
| Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Tr | iangle: |
| 3.500 inches single mounting facility single center group | |
| Winding Operating Voltage: | |
| 6.30 ac volts single component 2nd secondary | |
| Terminal Type And Quantity: | |
| 7 standoff, solder lug | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| | |

No

NSN 5950-00-764-1092

Power Transformer - Page 2 of 2

Fiig: A058b0

