

View Online at <https://aerobasegroup.com/nsn/5950-00-764-2073>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.125 inches single mounting facility single center group

Mounting Hole Diameter:

0.187 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

2.625 inches

Body Width:

2.500 inches

Body Height:

2.500 inches

Maximum Operating Temp:

95.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 6 secondary single component

Winding Operating Current:

6.5 milliamperes ac single component 1st secondary

Winding Operating Voltage:

52.00 ac volts single component 3rd secondary

Special Features:

1primary winding; 6secondary windings

Terminal Type And Quantity:

15 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0