

View Online at <https://aerobasegroup.com/nsn/5950-00-765-6411>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Vibration resistant and humidity resistant and explosion proof and fungus resistant and salt spray resistant

Frequency Rating:

400.0 hertz single component and 800.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Adjustment Device Drive Type:

Shaft single component

Body Length:

3.812 inches

Body Outside Diameter:

1.812 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing single group

Winding Function And Quantity:

1 primary, variable autotransformer type single component

Thread Size:

0.375 inches single group

Winding Operating Current:

2.5 amperes ac single component single primary output

Winding Power Rating:

70.0 volts-amperes single component single primary output

Adjustment Method And Quantity:

1 adjustable core single component

Winding Operating Voltage:

28.00 ac volts single component single primary output

Special Features:

Switch with 2 terminals; anti-lock pin; knob for shaft

Thread Series Designator:

Unef single group

Terminal Type And Quantity:

3 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0