

View Online at <https://aerobasegroup.com/nsn/5950-00-766-6441>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.296 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.859 inches single mounting facility single center group

Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

3.062 inches

Body Width:

2.625 inches

Body Height:

3.187 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

Winding Operating Current:

400.0 milliamperes ac single component 1st secondary

Winding Operating Voltage:

6.30 ac volts single component 2nd secondary

Special Features:

Internal shield brought out to terminal and core grounded to case and brought out to terminal

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

7 standoff, threaded stud and 1 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0