

View Online at <https://aerobasegroup.com/nsn/5950-00-767-1242>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.250 inches single mounting facility single center group

Mounting Hole Diameter:

0.120 inches single group

Frequency Rating:

45.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

4.500 inches

Body Width:

4.250 inches

Body Height:

3.750 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Winding Operating Current:

1.5 amperes dc single component 2nd secondary

Winding Operating Voltage:

46.00 ac volts single component 2nd secondary

Special Features:

Output currents stated as rectified

Terminal Type And Quantity:

12 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0