NSN 5950-00-767-2301

Reactor - Page 1 of 2

Reliability Indicator:

Not established



View Online at https://aerobasegroup.com/nsn/5950-00-767-2301

Overall Height:
0.895 inches
Inductance Type:
Fixed
Inductance Rating:
250.00 microhenries single component single winding
Frequency Rating:
1.0 kilohertz single component
Body Length:
Between 0.665 inches and 0.695 inches
Body Width:
Between 0.665 inches and 0.695 inches
Body Height:
Between 0.665 inches and 0.695 inches
Distance Between Mounting Facility Centers:
0.400 inches single mounting facility single center group
Winding Quantity:
1 single component
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
2 single group
2 single group Mounting Method:
Mounting Method:
Mounting Method: Threaded hole single group
Mounting Method: Threaded hole single group Rating Method:
Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding
Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi):
Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 56 single group
Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 56 single group Thread Size:
Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 56 single group Thread Size: 0.086 inches single group
Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 56 single group Thread Size: 0.086 inches single group Winding Operating Current:
Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 56 single group Thread Size: 0.086 inches single group Winding Operating Current: 1.0 amperes dc single component single winding
Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 56 single group Thread Size: 0.086 inches single group Winding Operating Current: 1.0 amperes dc single component single winding Dc Resistance Rating In Ohms:
Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 56 single group Thread Size: 0.086 inches single group Winding Operating Current: 1.0 amperes dc single component single winding Dc Resistance Rating In Ohms: 0.400 single component single winding
Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 56 single group Thread Size: 0.086 inches single group Winding Operating Current: 1.0 amperes dc single component single winding Dc Resistance Rating In Ohms: 0.400 single component single winding Thread Series Designator:
Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 56 single group Thread Size: 0.086 inches single group Winding Operating Current: 1.0 amperes dc single component single winding Dc Resistance Rating In Ohms: 0.400 single component single winding Thread Series Designator: Unc single group
Mounting Method: Threaded hole single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 56 single group Thread Size: 0.086 inches single group Winding Operating Current: 1.0 amperes dc single component single winding Dc Resistance Rating In Ohms: 0.400 single component single winding Thread Series Designator: Unc single group Terminal Type And Quantity:

NSN 5950-00-767-2301

Reactor - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A058b0