## NSN 5950-00-768-0757

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-768-0757

## **Reliability Indicator:**

Not established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.250 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.250 inches single mounting facility single center group

#### **Overall Height:**

1.380 inches

## **Overall Width:**

1.380 inches

#### Frequency Rating:

400.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### **Winding Shielding Method:**

Internal shield brought out to terminal single component

#### **Body Length:**

1.500 inches

## **Maximum Operating Temp:**

100.0 degrees celsius

#### **Inclosure Type:**

Open

#### **Mounting Facility Quantity:**

4 single group

#### **Mounting Method:**

Threaded hole single group

## **Winding Function And Quantity:**

1 primary single component and 1 secondary single component

#### Thready Qty Per Inch (tpi):

32 single group

#### **Thread Size:**

0.138 inches single group

#### **Winding Operating Current:**

700.0 milliamperes ac single component single secondary

#### **Winding Operating Voltage:**

26.00 ac volts single component single secondary

#### **Thread Series Designator:**

Unc single group

### **Terminal Type And Quantity:**

5 tab, solder lug

## Shelf Life:

N/a

# NSN 5950-00-768-0757

Power Transformer - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A058b0