NSN 5950-00-771-1609

Power Transformer - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5950-00-771-1609 |
|--|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.062 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 0.875 inches single mounting facility single center group |
| Mounting Hole Diameter: |
| 0.156 inches single group |
| Frequency Rating: |
| 400.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Winding Shielding Method: |
| Internal shield grounded to inclosure and core single component |
| Body Length: |
| 1.688 inches |
| Body Width: |
| 1.219 inches |
| Body Height: |
| 1.500 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Flange single group and unthreaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 2 secondary single component |
| Winding Operating Current: |
| 20.0 milliamperes dc single component all secondary |
| Winding Operating Voltage: |
| 24.00 ac volts single component single primary and 230.00 ac volts single component single primary |
| Terminal Type And Quantity: |
| 8 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - - |
| Demilitarization: |
| No |
| Fiig: |

A058b0