Power Autotransformer Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-774-8585

Reliability Indicator:Not establishedCenter To Center Distance Between Mounting Facilities Parallel To Length:12.500 inches single mounting facility single center groupCenter To Center Distance Between Mounting Facilities Parallel To Width:4.500 inches single mounting facility single center groupMounting Hole Diameter:0.375 inches single groupFrequency Rating:50.0 hertz single component and 60.0 hertz single componentInput-output Phase Relationship:Three phase to three phase single componentBody Length:
Center To Center Distance Between Mounting Facilities Parallel To Length: 12.500 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 4.500 inches single mounting facility single center group Mounting Hole Diameter: 0.375 inches single group Frequency Rating: 50.0 hertz single component and 60.0 hertz single component Input-output Phase Relationship: Three phase to three phase single component Body Length:
 12.500 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 4.500 inches single mounting facility single center group Mounting Hole Diameter: 0.375 inches single group Frequency Rating: 50.0 hertz single component and 60.0 hertz single component Input-output Phase Relationship: Three phase to three phase single component Body Length:
Center To Center Distance Between Mounting Facilities Parallel To Width: 4.500 inches single mounting facility single center group Mounting Hole Diameter: 0.375 inches single group Frequency Rating: 50.0 hertz single component and 60.0 hertz single component Input-output Phase Relationship: Three phase to three phase single component Body Length:
 4.500 inches single mounting facility single center group Mounting Hole Diameter: 0.375 inches single group Frequency Rating: 50.0 hertz single component and 60.0 hertz single component Input-output Phase Relationship: Three phase to three phase single component Body Length:
Mounting Hole Diameter: 0.375 inches single group Frequency Rating: 50.0 hertz single component and 60.0 hertz single component Input-output Phase Relationship: Three phase to three phase single component Body Length:
0.375 inches single group Frequency Rating: 50.0 hertz single component and 60.0 hertz single component Input-output Phase Relationship: Three phase to three phase single component Body Length:
Frequency Rating: 50.0 hertz single component and 60.0 hertz single component Input-output Phase Relationship: Three phase to three phase single component Body Length:
50.0 hertz single component and 60.0 hertz single component Input-output Phase Relationship: Three phase to three phase single component Body Length:
Input-output Phase Relationship: Three phase to three phase single component Body Length:
Three phase to three phase single component Body Length:
Body Length:
13.500 inches
Body Width:
7.125 inches
Body Height:
7.938 inches
Inclosure Type:
Open
Mounting Facility Quantity:
4 single group
Mounting Method:
Flange single group and unthreaded hole single group
Winding Function And Quantity:
1 primary, fixed autotransformer type single component
Winding Operating Current:
25.0 amperes ac single component single primary input
Winding Operating Voltage:
250.00 ac volts single component single primary input
Terminal Type And Quantity:
24 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A058b0