

View Online at <https://aerobasegroup.com/nsn/5950-00-775-1672>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Fungus proof and moisture resistant

Overall Length:

2.125 inches

Mounting Hole Diameter:

0.188 inches single group

Frequency Rating:

360.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

1.562 inches

Body Width:

3.750 inches

Body Height:

1.250 inches

Distance Between Mounting Facility Centers:

1.750 inches single mounting facility single center group

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Winding Operating Current:

600.0 milliamperes ac single component 1st secondary

Winding Operating Voltage:

84.00 ac volts single component single primary and 115.00 ac volts single component single primary and 121.00 ac volts single component single primary

Terminal Type And Quantity:

9 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0