## NSN 5950-00-775-1672

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-775-1672
Reliability Indicator:
Not established
Hazardous Locations/environmental Protection:
Fungus proof and moisture resistant
Overall Length:
2.125 inches
Mounting Hole Diameter:
0.188 inches single group
Frequency Rating:
360.0 hertz single component and 420.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield brought out to terminal single component
Body Length:
1.562 inches
Body Width:
3.750 inches
Body Height:
1.250 inches
Distance Between Mounting Facility Centers:
1.750 inches single mounting facility single center group
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
2 single group
Mounting Method:
Unthreaded hole single group
Winding Function And Quantity:
1 primary single component and 2 secondary single component
Winding Operating Current:
600.0 milliamperes ac single component 1st secondary
Winding Operating Voltage:
84.00 ac volts single component single primary and 115.00 ac volts single component single primary and 121.00 ac volts single component
single primary
Terminal Type And Quantity:
9 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 5950-00-775-1672

Power Transformer - Page 2 of 2



Fiig:

A058b0