

View Online at <https://aerobasegroup.com/nsn/5950-00-775-1686>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Fungus proof and moisture resistant

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.406 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.688 inches single mounting facility single center group

Mounting Hole Diameter:

0.156 inches single group

Frequency Rating:

360.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

1.875 inches

Body Width:

2.125 inches

Body Height:

1.875 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

1.1 amperes ac single component single secondary

Winding Operating Voltage:

56.00 ac volts single component single secondary

Terminal Type And Quantity:

7 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0