## NSN 5950-00-776-3280

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-776-3280

## **Reliability Indicator:**

Not established

## Center To Center Distance Between Mounting Facilities Parallel To Length:

2.719 inches single mounting facility single center group

### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.375 inches single mounting facility single center group

## Frequency Rating:

400.0 hertz single component

## Input-output Phase Relationship:

Three phase to three phase single component

## **Transformer Winding Connection Type:**

Wye-wye

### **Winding Shielding Method:**

Internal shield grounded to inclosure single component

### **Body Length:**

4.320 inches

### **Body Width:**

3.900 inches

## **Body Height:**

2.500 inches

## Inclosure Type:

Hermetically sealed

## **Mounting Facility Quantity:**

4 single group

## **Mounting Method:**

Threaded hole single group

## **Winding Function And Quantity:**

1 primary single component and 5 secondary single component

### **Thread Size:**

0.164 inches single group

## **Winding Operating Current:**

5.25 amperes dc single component 2nd secondary

## **Winding Operating Voltage:**

55.00 dc volts single component 2nd secondary

### **Special Features:**

1 primary winding; 5 secondary windings

## **Thread Series Designator:**

Unc single group

## **Terminal Type And Quantity:**

18 tab, solder lug

## Shelf Life:

N/a

# **NSN 5950-00-776-3280**Power Transformer - Page 2 of 2



| ш | ın | 10 | <i>(</i> )+ | Measure: |  |
|---|----|----|-------------|----------|--|
|   |    |    |             |          |  |

Demilitarization:

No

Fiig:

A058b0