

View Online at <https://aerobasegroup.com/nsn/5950-00-778-8608>

**Reliability Indicator:**

Not established

**Hazardous Locations/environmental Protection:**

Fungus proof and moisture resistant

**Frequency Rating:**

360.0 hertz single component and 420.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to core single component

**Body Length:**

1.125 inches

**Body Width:**

0.969 inches

**Body Height:**

0.938 inches

**Distance Between Mounting Facility Centers:**

0.813 inches single mounting facility single center group

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

2 single group

**Mounting Method:**

Threaded hole single group

**Winding Function And Quantity:**

1 primary single component and 2 secondary single component

**Thread Size:**

0.112 inches single group

**Winding Operating Current:**

40.0 milliamperes ac single component all secondary

**Winding Operating Voltage:**

75.00 ac volts single component single primary and 115.00 ac volts single component single primary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

10 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0