

View Online at <https://aerobasegroup.com/nsn/5950-00-778-8624>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Fungus proof and moisture resistant

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.875 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

2.188 inches

Body Width:

1.688 inches

Body Height:

1.812 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

5.0 milliamperes ac single component 2nd secondary

Winding Operating Voltage:

78.00 ac volts single component single primary and 87.00 ac volts single component single primary and 96.00 ac volts single component single primary and 100.00 ac volts single component single primary and 109.00 ac volts single component single primary and 115.00 ac volts single component single primary and 121.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

12 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0