# NSN 5950-00-779-0046

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-779-0046

## **Reliability Indicator:**

Not established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

0.438 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.250 inches single mounting facility single center group

**Overall Height:** 

0.940 inches

**Overall Width:** 

0.760 inches

Frequency Rating:

400.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### **Winding Shielding Method:**

Internal shield brought out to terminal single component

#### **Body Length:**

1.500 inches

## **Maximum Operating Temp:**

100.0 degrees celsius

# Inclosure Type:

Hermetically sealed

# **Mounting Facility Quantity:**

4 single group

#### **Mounting Method:**

Threaded hole single group

# **Winding Function And Quantity:**

1 primary single component and 1 secondary single component

#### Thready Qty Per Inch (tpi):

40 single group

#### **Thread Size:**

0.112 inches single group

#### **Winding Operating Current:**

400.0 milliamperes ac single component single secondary

#### **Winding Operating Voltage:**

6.30 ac volts single component single secondary

#### **Thread Series Designator:**

Unc single group

#### **Terminal Type And Quantity:**

6 tab, solder lug

# Shelf Life:

N/a

# **NSN 5950-00-779-0046**Power Transformer - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

Demilitarization:

No

Fiig:

A058b0