## NSN 5950-00-780-8605

Power Autotransformer Transformer - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5950-00-780-8605             |
|---|
| Reliability Indicator:  |
| Not established   |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.188 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 1.188 inches single mounting facility single center group                 |
| Mounting Hole Diameter:   |
| 0.156 inches single group   |
| Frequency Rating:   |
| 360.0 hertz single component and 440.0 hertz single component             |
| Input-output Phase Relationship:  |
| Single phase to single phase single component                             |
| Body Length:  |
| 1.423 inches  |
| Body Width:   |
| 1.423 inches  |
| Body Height:  |
| 2.469 inches  |
| Inclosure Type:   |
| Hermetically sealed   |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Flange single group and unthreaded hole single group                      |
| Winding Function And Quantity:  |
| 1 primary, fixed autotransformer type single component                    |
| Winding Operating Current:  |
| 500.0 milliamperes ac single component single primary output              |
| Winding Operating Voltage:  |
| 68.00 ac volts single component single primary output                     |
| Terminal Type And Quantity:   |
| 4 tab, solder lug   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |

Fiig:

A058b0