

View Online at <https://aerobasegroup.com/nsn/5950-00-782-8196>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Salt spray resistant

Overall Length:

Between 2.030 inches and 2.150 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.365 inches single mounting facility single center group and 1.385 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.115 inches single mounting facility single center group and 1.135 inches single mounting facility single center group

Overall Height:

Between 2.320 inches and 2.440 inches

Overall Width:

Between 1.630 inches and 1.750 inches

Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internally shielded single component

Maximum Operating Temp:

95.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 5 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

500.0 milliamperes ac single component 3rd secondary

Winding Operating Voltage:

33.00 ac volts single component 4th secondary

Special Features:

1 primary winding; 5 secondary windings; 5th winding is center-tapped

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

14 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0