

View Online at <https://aerobasegroup.com/nsn/5950-00-782-8196>

**Reliability Indicator:**

Not established

**Hazardous Locations/environmental Protection:**

Salt spray resistant

**Overall Length:**

Between 2.030 inches and 2.150 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.365 inches single mounting facility single center group and 1.385 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.115 inches single mounting facility single center group and 1.135 inches single mounting facility single center group

**Overall Height:**

Between 2.320 inches and 2.440 inches

**Overall Width:**

Between 1.630 inches and 1.750 inches

**Frequency Rating:**

380.0 hertz single component and 420.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internally shielded single component

**Maximum Operating Temp:**

95.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded hole single group

**Winding Function And Quantity:**

1 primary single component and 5 secondary single component

**Thread Size:**

0.138 inches single group

**Winding Operating Current:**

500.0 milliamperes ac single component 3rd secondary

**Winding Operating Voltage:**

33.00 ac volts single component 4th secondary

**Special Features:**

1 primary winding; 5 secondary windings; 5th winding is center-tapped

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

14 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0