## NSN 5950-00-785-6531

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-785-6531

| Reliability Indicator:  |
|---|
| Not established   |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.125 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 1.530 inches single mounting facility single center group                 |
| Frequency Rating:   |
| 400.0 hertz single component  |
| Input-output Phase Relationship:  |
| Single phase to single phase single component                             |
| Body Length:  |
| 3.770 inches  |
| Body Width:   |
| 2.310 inches  |
| Body Height:  |
| 2.690 inches  |
| Maximum Operating Temp:   |
| 130.0 degrees celsius   |
| Inclosure Type:   |
| Hermetically sealed   |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Threaded hole single group  |
| Winding Function And Quantity:  |
| 1 primary single component and 1 secondary single component               |
| Thread Size:  |
| 0.138 inches single group   |
| Winding Operating Voltage:  |
| 20.00 ac volts single component single secondary                          |
| Thread Series Designator:   |
| Unc single group  |
| Terminal Type And Quantity:   |
| 103 tab, solder lug   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |

A058b0