

View Online at <https://aerobasegroup.com/nsn/5950-00-787-4835>

Thread Class (non-core):

2a single group

Thread Direction (non-core):

Right-hand single group

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.062 inches single mounting facility single center group

Frequency Rating:

50.0 hertz and 70.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

3.000 inches

Body Width:

3.375 inches

Body Height:

2.500 inches

Inclosure Type:

Partially enclosed, double shell

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary and 4 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.125 inches single group

Winding Operating Current:

600.0 milliamperes ac single component 2nd secondary

Winding Operating Voltage:

6.30 ac volts single component 3rd secondary

Thread Series Designator:

Uns single group

Terminal Type And Quantity:

13 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0