

View Online at <https://aerobasegroup.com/nsn/5950-00-788-6828>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.062 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.062 inches single mounting facility single center group

Frequency Rating:

57.0 hertz single component and 63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

3.500 inches

Body Width:

2.312 inches

Body Height:

3.500 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Rating Method:

Electrical single component single secondary

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

50.0 milliamperes dc single component all winding and 250.0 milliamperes dc single component all winding

Dc Resistance Rating In Ohms:

40.000 single component single secondary

Winding Operating Voltage:

40.00 dc volts single component all winding

Special Features:

Reactor part of component has 2 windings

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0