

View Online at <https://aerobasegroup.com/nsn/5950-00-789-1886>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.313 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.875 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

3.062 inches

Body Width:

2.625 inches

Body Height:

3.187 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

Winding Operating Current:

20.0 milliamperes dc single component 1st secondary and 400.0 milliamperes dc single component 1st secondary

Criticality Code Justification:

Zzzy

Winding Operating Voltage:

54.00 ac volts single component 3rd secondary

Special Features:

50v secondary shielded from all other windings and brought out to terminal

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 standoff, solder lug

Reference Number Differentiating Characteristics:

Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A058b0