NSN 5950-00-789-5305

Audio Frequency Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-789-5305

| R | e۱ | lia | h | ili | it۷ | , 1 | n | d | i | са | t | n | r | |
|---|----|-----|---|-----|-----|-----|---|---|---|----|---|---|---|--|
| П | CI | IIa | v | ш | ıι١ | , , | ш | u | ľ | υa | u | u | ı | |

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.046 inches single mounting facility single center group and 2.078 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.422 inches single mounting facility single center group and 1.454 inches single mounting facility single center group

Mounting Hole Diameter:

0.188 inches single group

Impedance Rating In Ohms:

114.0 single component single primary and 125.0 single component single primary

Frequency Rating:

100.0 hertz single component and 5.0 kilohertz single component

Body Length:

Between 2.422 inches and 2.454 inches

Body Width:

Between 1.796 inches and 1.828 inches

Body Height:

Between 1.672 inches and 1.704 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

4.0 milliamperes ac single component single secondary

Terminal Type And Quantity:

5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A058b0