

View Online at <https://aerobasegroup.com/nsn/5950-00-789-9657>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.640 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.140 inches single mounting facility single center group

Frequency Rating:

57.0 hertz single component and 63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component and internal shield grounded to core and brought out to terminal single component

Body Length:

3.562 inches

Body Width:

3.062 inches

Body Height:

4.875 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

Winding Operating Current:

250.0 milliamperes ac single component single secondary

Winding Operating Voltage:

280.00 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0