

View Online at <https://aerobasegroup.com/nsn/5950-00-790-4130>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.750 inches single mounting facility single center group

Mounting Hole Diameter:

0.188 inches single group

Frequency Rating:

50.0 hertz single component and 1.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

3.750 inches

Body Width:

3.250 inches

Body Height:

2.875 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

2 primary single component and 7 secondary single component

Winding Operating Current:

300.0 milliamperes dc single component 4th secondary

Winding Power Rating:

5.25 volts-amperes single component 3rd secondary

Winding Operating Voltage:

4.50 ac volts single component 2nd secondary

Special Features:

Two primary windings and seven secondary windings

Terminal Type And Quantity:

22 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0