NSN 5950-00-794-2866

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-794-2866

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.500 inches single mounting facility single center group

Mounting Hole Diameter:

0.125 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

15.0 decibels single component

Adjustment Device Drive Type:

Slotted screw single component

Body Length:

2.250 inches

Body Width:

2.000 inches

Body Height:

3.062 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

27.0 milliamperes ac single component single primary

Winding Power Rating:

75.0 milliwatts single component single secondary

Adjustment Method And Quantity:

1 adjustable control single component

Winding Operating Voltage:

18.00 ac pounds per hour wet single component single primary

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

NSN 5950-00-794-2866Power Transformer - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

Demilitarization:

No

Fiig:

A058b0