

View Online at <https://aerobasegroup.com/nsn/5950-00-800-1148>

**Reliability Indicator:**

Not established

**Impedance Rating In Ohms:**

1200.0 single component single secondary

**Frequency Rating:**

200.0 hertz single component and 15.0 kilohertz single component

**Maximum Transformer Power Rating:**

22.0 decibels single component

**Body Length:**

1.000 inches

**Body Width:**

1.000 inches

**Body Height:**

1.375 inches

**Distance Between Mounting Facility Centers:**

1.125 inches single mounting facility single center group

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

2 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Thread Qty Per Inch (tpi):**

32 single group

**Thread Size:**

0.138 inches single group

**Winding Operating Current:**

3.0 milliamperes dc single component single primary

**Test Data Document:**

81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

5 standoff, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0